

## 100 liter tank i Syrafast 316



**60 000 SEK /st exkl moms**

**Article type:** second-hand mixing tank

**Additional information:** never been used, absolutely new condition, new agitators 0.75kW 220Volt mono; we can't give any guarantees about the agitator

**Volumetric volume (L):** 100 L

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 316L (V4A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Shape of tank:** cylindrical

**Bottom type:** dished

**Total discharge:** yes

**Fixation points:** 3 non adjustable feet

**Fixation point(s):** RVS 304L

**Suitable for food industry:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Tank outlet:** inside Ø 50 mm

**Outlet type:** DIN11851

**Agitator:** yes

**Agitator type:** propeller agitator

**Position engine:** at the top

**Number of revolutions:** 1.400

**Power:** 0,75

**Voltage:** mono

**Top:** 5 mm

**Cylinder:** 3 mm

**Bottom:** 3 mm

**Internal diameter tank:** 445 mm

**Distance from outlet to ground:** 260 mm

**Outer diameter tank:** 500 mm

**Cylinder height:** 640 mm

**Total height of tank:** 1.370 mm

**Empty weight tank:** 100

**SKU:** 26676

## Mer information

### Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: never been used, absolutely new condition, new agitators 0.75kW 220Volt mono; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: dished

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316L (V4A)

Volym i liter: 100

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 50 mm

Teknisk ritning finns: Nej

Utloppstyp: DIN11851



## Översikt material

Material: Syrafast 316

Fixeringspunkt(er): RVS 304L

## Dimensioner av tank

Cylinderhöjd: 640 mm

Invändig diameter: 445 mm

Mått utlopp till marken: 260 mm

Total höjd: 1.370 mm

Ytterdiameter: 500 mm

## Omrörare

Kraft (kW): 0,75

Position motor: at the top

Typ av omrörare: propeller agitator

Varvtal: 1.400

Spänning (Volt): mono

## Tjocklek på tank

Botten: 3 mm

Cylinder: 3 mm

Topp: 5 mm

## Mer

Isolerad: Nej

Vikt: 100