

100 liter tank i Syrafast 316



136 000 SEK /st exkl moms

item available on order

Article type: brand new mixing tank - type VC-HILA

Additional information: delivered with food certificate; *article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);* Ra=<0.8µm

Volumetric volume (L): 100 L

Max. density P (kg/m³): 1.200

Ra inner weld: 0,80

Finish stainless steel: 2b

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 100 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Top type: half hinging lid °

Shape of tank: cylindrical

Bottom type: conical 10 °

Total discharge: yes

Fixation points: 3 non adjustable feet

Type of HE on the cylinder: dimple-jacket

Position HE: the complet cilinder

Height HE: 375 mm

Number of sections: 1

Water pressure HE: 3 Bar

Hydraulic test pressure: 4,50 Bar

Contact surface cylinder: 0,55 m²



Working temperature HE cylinder: 100 °C

Type HE: dimple jacket on the bottom

Heat exchanger: RVS 304

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304L

Gasket manway(s): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: yes

CIP spray ball: no, optional

Tank outlet: inside Ø 40 mm

Outlet type: DIN11851

Total outlet valve: no, optional

Agitator: no, optional

Agitator type: propeller agitator

Position engine: at the top

Number of revolutions: 1.410

Voltage: 400 V - three-phase

Agitator type 2: propeller agitator

Position engine: at the top

Number of revolutions: 750

Voltage: 400 V - three-phase

Top: 3 mm

Cylinder: 3 mm

Bottom: 3 mm

Cylinder: 2

Insulation body: yes

finish of the outer jacket: welded

Insulation thickness: 40



Internal diameter tank: 500 mm

Distance from outlet to ground: 250 mm

Outer diameter tank: 580 mm

Cylinder height: 500 mm

Total height of tank: 1.500 mm

Empty weight tank: 95

SKU: 6902

Mer information



Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetstryck i tank: ATM – atmosferic

Finish rostfritt stål: 2b

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 100 °C

Maximal densitet för produkten: 1200

Min. arbetstemperatur: -10 °C

Mobil tank: Nej

Övrig information: delivered with food certificate; article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);

Övrig information2: Ra=<0.8µm

Omrörare: Nej

Ra innersvets: 0,80

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical 10 °

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 100

Utrustning

Fläns för omrörare: Ja

Märkskylt: Ja

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 40 mm

Teknisk ritning finns: Ja

Utloppstyp: DIN11851

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: Rockwool
Ytterbeklädnad: RVS 304

Dimensioner av tank

Cylinderhöjd: 500 mm
Invändig diameter: 500 mm
Mått utlopp till marken: 250 mm
Total höjd: 1.500 mm
Ytterdiameter: 580 mm

Värmeväxlare

Arbetstemperatur värmeväxlare cylinder: 100 °C
Höjd värmeväxlare: 375 mm
Hydrauliskt provtryck botten: 4,50 Bar
Hydrauliskt provtryck: 4,50 Bar
Kontaktyta cylinder: 0,55 m²
Position värmeväxlare: the complet cilinder
Typ av värmeväxlare på cylinder: dimple-jacket
Vattentryck värmeväxlare: 3 Bar

Omrörare

Position motor: at the top
Typ av omrörare: propeller agitator
Varvtal: 1.410
Spänning (Volt): 400 V – three-phase

Tjocklek på tank

Botten: 3 mm
Cylinder: 3 mm
Topp: 3 mm

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded

Isolering mantel: Ja

Isoleringsmaterial: Rockwool

Mer

Värmeväxlare: RVS 304

Cylinder OW: 2

Isoleringstjocklek OW: 40

Isolerad: Ja

Vikt: 95