








G-G 1 : 2







B 1 : 4





D-D 1 : 10






Schnellmischer:
1.RW9532V6N 0,25kW 1500rpm 400V
2.RW9533V6N 0,12kW 680rpm 400V







Item	Description	PN MPa	DN mm.	Qty.
A1	TUBULAR LEG ON WHEEL WITHOUT BREAK - AISI 304L	-	-	2
B1	TUBULAR LEG ON WHEEL WITH BREAK - AISI 304L	-	-	2
C1	1/2 FIXED LID - AISI 316L	-	-	1
D1	1/2 HINGED LID - AISI 316L	-	-	1
E1	CONICAL INLET FOR AGITATOR UP TO FLANGE; ∅220mm; s20 - AISI 316L -agitator and mounting of the agitator are not included	atm.	100	1
F1	HOLDER FOR PUSHING THE TANK - AISI 304L	-	-	1
G1	DISMOUNTABLE STATIC CIP SPRAY BALL Φ28 360° UP TO WELDING MALE NIPPLE - AISI 316L	atm.	G1/2"	1
H1	TIGHTNER FOR HINGED LID	-	-	2
I1	DISMOUNTABLE TOTAL OUTLET UP TO WELDING LINER AND NUT DIN 11851 - AISI 316L	atm.	40	1
J1	SAFETY GRID 412x187 ON HINGED LID - AISI 316L	-	-	1

Surface	Outside	2B	Welding seam	Outside	strip grinded to Ra<1,6
	Inside	2B		Inside	flat grinded to Ra<0,8

1.6 | min.0,5x45° | **Not-indicated tolerances of dimensions of length and angles, shapes and positions are according to EN ISO 13920:2006**

Drawn.: **I.N.**	Scale 1:13	Mass 75.0	AISI 316L AISI 304L	
Checket: **K.I.**				=0.1m3
Eng.App.: **D.M.**		20.11.2015 г.		Sheet 1/1