

## 100 liter tank i Syrafast 316



**110 000 SEK /st exkl moms**

item available on order

**Article type:** brand new mixing tank - type VC-SCA

**Additional information:** delivered with food certificate; *article price without agitator*; choice of 2 different types of agitators; see options; (The article can also be purchased without options);  $Ra < 0.8 \mu m$

**Volumetric volume (L):** 100 L

**Max. density P (kg/m<sup>3</sup>):** 1.200

**Ra inner weld:** 0,80

**Finish stainless steel:** 2b

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 80 °C

**Min. temperature (°C):** -10 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** yes

**Top type:** half hinging lid °

**Shape of tank:** cylindrical

**Bottom type:** conical 10 °

**Total discharge:** yes

**Fixation points:** 4 casters

**Fixation point(s):** RVS 304

**Suitable for food industry:** yes

**Documents included:** yes, optional

**Technical drawing included:** yes

**Registration plate on the tank:** yes

**Flange for agitator:** yes

**CIP spray ball:** no, optional

**Tank outlet:** inside Ø 40 mm

**Outlet type:** DIN11851

**Total outlet valve:** no, optional

**Agitator:** no, optional

**Outer diameter tank:** 500 mm

**Total height of tank:** 1.500 mm

**Empty weight tank:** 65

SKU: 7550

## Mer information

### Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetstryck i tank: ATM – atmosferic

Finish rostfritt stål: 2b

Konfiguration: single-skin

Max. arbetstemperatur: 80 °C

Maximal densitet för produkten: 1200

Min. arbetstemperatur: -10 °C

Mobil tank: Ja

Övrig information: delivered with food certificate; article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);

Övrig information2: Ra=<0.8µm

Omrörare: Nej

Ra innersvets: 0,80

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical 10 °

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 100

## Utrustning

Fläns för omrörare: Ja  
Märkskylt: Ja  
Livsmedelsklassad: Ja  
Tankutlopp: inside Ø 40 mm  
Teknisk ritning finns: Ja  
Utloppstyp: DIN11851

## Översikt material

Material: Syrafast 316  
Fixeringspunkt(er): RVS 304

## Dimensioner av tank

Total höjd: 1.500 mm  
Ytterdiameter: 500 mm

## Mer

Isolerad: Nej  
Vikt: 65