100 liter tank i Syrafast 316



69 000 SEK /st exkl moms

Additional information: pharmacy; control cabinet (without guarantee of function)
Volumetric volume (L): 100 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,50 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Max Overpressure: 3,50 Bar
Max onderdruk: 1 Bar

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: 15

Agitator: yes
Number of revolutions: 558
Power: 0,25
Internal diameter tank: 450 mm
Cylinder height: 600 mm

Total height of tank: 1.700 mm
Total outer width: 800 mm
Total outer length: 1.300 mm

SKU: 389888

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: pharmacy; control cabinet (without guarantee of function); we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3,50 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 100

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 600 mm
Invändig diameter: 450 mm
Total höjd: 1.700 mm

Omrörare
Kraft (kW): 0,25
Varvtal: 558

Mer
Isolerad: Nej