1000 liter tank i Rostfritt 304



179 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: tank has never been used: welds polished Ra 0.8; agitator completely stainless-steel; we can't give any guarantees about the agitator
Volumetric volume (L): 1.000 L
Max. density P (kg/m³): 1.200
Pressure in tank: ATM - atmosferic

Max. temperature (°C): 80 °C
Material wet parts: SS AISI 304 (V2A)
Model: vertical
Configuration: single-skin

Heat exchanger: no

Insulation: no
Mobile tank: no
Top type: conical 15 °
Shape of tank: cylindrical
Bottom type: conical 15

Total discharge: yes
Fixation points: 3 non adjustable feet
Legs: Set of baseplates and adjusting pieces included
Spray ball: RVS 304
Manway(s): RVS 304

Gasket manway(s): unknown
Fixation point(s): RVS 304
Wet parts agitator(s): SS AISI 304 (V2A)
Suitable for food industry: no
Documents included: no

Technical drawing included: yes
Registration plate on the tank: no
Flange for agitator: yes
CIP spray ball: no
Tank outlet: inside Ø 50 mm

Outlet type: DIN11850 male
Total outlet valve: no
Adjustable legs: yes
Agitator: yes
Agitator type: propeller agitator

Position engine: at the top
Number of revolutions: 1.425
Power: 2,20
Voltage: three-phase
Top: 3 mm

Cylinder: 3 mm
Bottom: 3 mm

Distance from outlet to ground: 280 mm
Outer diameter tank: 1.450 mm
Cylinder height: 630 mm

Total height of tank: 2.100 mm
Total outer width: 1.600 mm
Total outer length: 1.900 mm
Empty weight tank: 350

SKU: 378131

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: single-skin
Max. arbetstemperatur: 80 °C
Maximal densitet för produkten: 1200
Mobil tank: Nej
Övrig information: tank has never been used: welds polished Ra 0.8; agitator completely stainless-steel; we can't give any guarantees about the agitator
Omrörare: Ja
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical 15
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 1000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Ja
Märkskylt: Nej
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN11850 male
Utloppsventil: Nej

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Dimensioner av tank

Cylinderhöjd: 630 mm
Mått utlopp till marken: 280 mm
Total höjd: 2.100 mm
Ytterdiameter: 1.450 mm

Omrörare

Kraft (kW): 2,20
Position motor: at the top
Typ av omrörare: propeller agitator
Varvtal: 1.425
Spänning (Volt): three-phase

Tjocklek på tank

Botten: 3 mm
Cylinder: 3 mm
Topp: 3 mm

Mer

Isolerad: Nej
Vikt: 350