



Revisions					
Rev	Description	Date	Drawn	Checked	Rev. DD









Geometrical volume	1000 ℓ
Working pressure	Atmospheric
Working temperature	-10/80°C
Maximum density	1.2kg/dm³
Tare mass	117 kg
Equipment output/voltage	-

Geometrical volume - jacket	-
Working pressure - jacket	-
Working temperature - jacket	-
Jacket pressure drop	-
Material	1.4307/ AISI 304L
Year of manufacture	

Item	Description	PN bar	DN mm.	Qty.
A	LEG ON ADJUSTABLE SUPPORT	-	-	3
B	INLET DN50 ON TANK TOP UP TO WELDING MALE DN50 DIN11851	atm.	50	1
C	UPPER MANHOLE DN400 Elica art.40/1p-4 WITH EPDM-FDA-GASKET	atm.	400	1
D	INLET DN80 CENTRICALLY MOUNTED ON TANK TOP UP TO WELDING MALE DN80 DIN11851	atm.	80	1
E	INLET AIRVENT DN65 ON TANK TOP UP TO WELDING MALE DN65 DIN11851	atm.	65	1
F	TOTAL OUTLET DN50 UP TO WELDING MALE DN50 DIN11851	atm.	50	1

Straightness, flatness and parallelism - EN 13920 F								Linear dimensions - EN 13920 B							
≥30 ≤120	>120 ≤400	>400 ≤1000	>1000 ≤2000	>2000 ≤4000	>4000 ≤8000	>8000 ≤12000	>12000 ≤16000	≥2 ≤30	>30 ≤400	>400 ≤1000	>1000 ≤2000	>2000 ≤4000	>4000 ≤8000	>8000 ≤12000	>12000 ≤16000
1	1.5	3	4.5	6	8	10	12	±1	±2	±3	±4	±6	±8	±10	±12

Surface	Outside	Matt 2B	Weld. seams	Outside: Strip grinded 2x20 Ra<1,6
	Inside	Matt 2B		Inside: Flat grinded to Ra<0,8

1.6	Drawn: **I.N.**	Scale 1:18	Weight 117	1.4307/ AISI 304L	
	Checked: **K.I.**				1000L
	Approved: **D.M.**		Rev	Lang Eng	Sheet 1/1