

1000 liter tank i Rostfritt 304



49,000,00 kr /st exkl moms

item available on order

Article type: brand new palletized transporttank (not ADR) - type IBC-AZ/F1

Additional information: This is a palletized container: design pressure -0.15/+2 bar; operational pressure +0.49 bar. We can take more containers in production for you.

Volumetric volume (L): 1.000 L

Max. density P (kg/m³): 1.600

Pressure in tank: pressure

Max. pressure (Bar): 0,49 Bar

Min. pressure (Bar): 0,15 Bar
Material wet parts: SS AISI 304 (V2A)
Model: vertical
Configuration: single-skin

Heat exchanger: no
Insulation: no
Mobile tank: yes
Top type: dished
Shape of tank: cylindrical

Bottom type: conical 30 °
Total discharge: yes
Fixation points: 4 stackable frame
Manway(s): RVS 304
Gasket manway(s): parra rubber

Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes
Registration plate on the tank: yes

Flange for agitator: no
Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 400 mm
Hinged lid: yes

CIP spray ball: no
Tank outlet: inside Ø 50 mm
Outlet type: DIN11850
Total outlet valve: yes
Agitator: no, optional

Top: 2,50 mm
Cylinder: 2 mm
Bottom: 2,50 mm
Distance from outlet to ground: 210 mm



Outer diameter tank: 1.000 mm

Cylinder height: 1.000 mm

Height of top: 230 mm

Height of bottom: 342 mm

Feet height: 456 mm

Total height of tank: 1.857 mm

Empty weight tank: 115

SKU: 5948

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetstryck i tank: pressure

Konfiguration: single-skin

Maximal densitet för produkten: 1600

Mobil tank: Ja

Övrig information: This is a palletized container: design pressure -0.15/+2 bar; operational pressure +0.49 bar. We can take more containers in production for you.

Omrörare: Nej

Övertryck: 0,49 Bar

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical 30 °

Undertryck (vakuum): 0,15 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 1000

Utrustning

Fläns för omrörare: Nej

Märkskylt: Ja

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 50 mm

Teknisk ritning finns: Ja

Utloppstyp: DIN11850

Utloppsventil: Ja

Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304



Dimensioner av tank

Cylinderhöjd: 1.000 mm
Höjd på fötter: 456 mm
Mått utlopp till marken: 210 mm
Total höjd: 1.857 mm
Ytterdiameter: 1.000 mm

Tjocklek på tank

Botten: 2,50 mm
Cylinder: 2 mm
Topp: 2,50 mm

Mer

Isolerad: Nej
Vikt: 115