1000 liter tank i Rostfritt 304



25 000 SEK /st exkl moms

Article type: second-hand transport tank
Additional information: Previous product was Methyl Acrylate (Cas. No. 96-33-3), the tanks are empty and cleaned; the tanks have not been used much and are in very good condition; UN marking.
Volumetric volume (L): 1.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes

Mobile tank: no

Top type: flat
Shape of tank: rectangular
Bottom type: flat sloping
Total discharge: yes
Fixation points: 4 stackable frame

Insulation material: Rockwool
Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 304
Fixation point(s): galvanised steel
Suitable for food industry: no

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1

Position of manway: at the top
Height manhole 1 (mm): 400 mm
Tank outlet: inside Ø 50 mm
Total outlet valve: yes
Top: 1,50 mm

Cylinder: 1,50 mm
Bottom: 1,50 mm
Distance from outlet to ground: 280 mm
Total height of tank: 1.750 mm
Total outer width: 1.010 mm

Total outer length: 1.210 mm
Empty weight tank: 280

SKU: 567839

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated
Mobil tank: Nej
Övrig information: Previous product was Methyl Acrylate (Cas. No. 96-33-3), the tanks are empty and cleaned; the tanks have not been used much and are in very good condition; UN marking.
Omrörare: Nej
Tankens form: rectangular
Total urtappning: Ja
Typ av botten: flat sloping
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 1000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Nej
Utloppsventil: Ja

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Översikt material
Material: Rostfritt 304
Fixeringspunkt(er): galvanised steel
Isoleringsmaterial: Rockwool
Ytterbeklädnad: RVS 304

Dimensioner av tank
Mått utlopp till marken: 280 mm
Total höjd: 1.750 mm

Tjocklek på tank
Botten: 1,50 mm
Cylinder: 1,50 mm
Topp: 1,50 mm

Tjocklek på ytterbeklädnad och isolering
Isoleringsmaterial: Rockwool

Mer
Isolerad: Ja
Vikt: 280

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se