1000 liter tank i Rostfritt 304



64 000 SEK /st exkl moms

Additional information: chemistry; handhole cover is missing
Volumetric volume (L): 1.000 L
Pressure in tank: pressure
Max. pressure (Bar): 0,50 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 0,50 Bar

Max. temperature (°C): 80 °C
Material wet parts: SS AISI 304 (V2A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 26 L
Max Overpressure: 1 Bar

Max. working temperature: 80 °C
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Heat exchanger: RVS 316
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: 25
Agitator: yes
Power: 1.5 / 4.5

Top: 18 mm
Cylinder: 4,80 mm
Bottom: 4,80 mm
Internal diameter tank: 1.150 mm
Cylinder height: 830 mm

Total height of tank: 2.400 mm

SKU: 446252

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 80 °C
Mobil tank: Nej
Övrig information: chemistry; handhole cover is missing; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 0,50 Bar
Total urtappning: Ja
Undertryck (vakuum): 0,50 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 1000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank
Cylinderhöjd: 830 mm
Invändig diameter: 1.150 mm
Total höjd: 2.400 mm

Omrörare
Kraft (kW): 1.5 / 4.5

Tjocklek på tank
Botten: 4,80 mm
Cylinder: 4,80 mm
Topp: 18 mm

Mer
Värmeväxlare: RVS 304
Isolerad: Nej