1000 liter tank i Rostfritt 304



95 000 SEK /st exkl moms

Article type: second-hand fermentation tank
Additional information: The tanks have never been used; we can't give any guarantees about the heating/cooling jacket
Volumetric volume (L): 1.000 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 20 °C

Min. temperature (°C): -10 °C
Material wet parts: SS AISI 304 (V2A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Top type: large seperat lid
Shape of tank: cylindrical
Bottom type: flat sloping

Total discharge: yes
Fixation points: 4 adjustable feet
Type of HE on the cylinder: dimple-jacket
Water pressure HE: 3 Bar
Type of HE on the bottom: dimple-jacket

Water pressure HE: 3 Bar
Heat exchanger: RVS 304
Outer jacket (ornamental wall): RVS 304
Fixation point(s): RVS 304
Suitable for food industry: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Tank outlet: inside Ø 32 mm

Outlet type: DIN11851 male
Total outlet valve: no
Agitator: no, optional
Internal diameter tank: 1.510 mm
Distance from outlet to ground: 270 mm

Outer diameter tank: 1.600 mm
Cylinder height: 870 mm
Total height of tank: 1.300 mm

SKU: 451085

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 20 °C
Min. arbetstemperatur: -10 °C
Mobil tank: Nej
Övrig information: The tanks have never been used; we can't give any guarantees about the heating/cooling jacket
Omrörare: Nej
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: flat sloping
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 1000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 32 mm
Teknisk ritning finns: Nej
Utloppstyp: DIN11851 male
Utloppsventil: Nej

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Ytterbeklädnad: RVS 304

Dimensioner av tank

Cylinderhöjd: 870 mm
Invändig diameter: 1.510 mm
Mått utlopp till marken: 270 mm
Total höjd: 1.300 mm
Ytterdiameter: 1.600 mm

Värmeväxlare

Typ av värmeväxlare på cylinder: dimple-jacket
Typ av värmeväxlare på botten: dimple-jacket
Vattentryck värmeväxlare: 3 Bar
Vattentryck värmeväxlare botten: 3 Bar

Mer

Värmeväxlare: RVS 304
Isolerad: Ja

Rodervägen 57
891 78 Bonässund
info@processoverskott.se