

## 1000 liter tank i Rostfritt 304



**94 000 SEK /st exkl moms**

**Article type:** second-hand fermentation tank

**Additional information:** The tanks have never been used; we can't give any guarantees about the heating/cooling jacket

**Volumetric volume (L):** 1.000 L

**Pressure in tank:** ATM - atmospheric

**Max. temperature (°C):** 20 °C

**Min. temperature (°C):** -10 °C

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes



**Insulation:** yes

**Mobile tank:** no

**Top type:** large seperat lid

**Shape of tank:** cylindrical

**Bottom type:** flat sloping

**Total discharge:** yes

**Fixation points:** 4 adjustable feet

**Type of HE on the cylinder:** dimple-jacket

**Water pressure HE:** 3 Bar

**Type of HE on the bottom:** dimple-jacket

**Water pressure HE:** 3 Bar

**Heat exchanger:** RVS 304

**Outer jacket (ornamental wall):** RVS 304

**Fixation point(s):** RVS 304

**Suitable for food industry:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Tank outlet:** inside Ø 32 mm

**Outlet type:** DIN11851 male

**Total outlet valve:** no

**Agitator:** no, optional

**Internal diameter tank:** 1.510 mm

**Distance from outlet to ground:** 270 mm

**Outer diameter tank:** 1.600 mm

**Cylinder height:** 870 mm

**Total height of tank:** 1.300 mm

**SKU:** 451085

## Mer information

### Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 20 °C

Min. arbetstemperatur: -10 °C

Mobil tank: Nej

Övrig information: The tanks have never been used; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: flat sloping

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 1000

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 32 mm

Teknisk ritning finns: Nej

Utloppstyp: DIN11851 male

Utloppsventil: Nej

## Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Ytterbeklädnad: RVS 304

## Dimensioner av tank

Cylinderhöjd: 870 mm

Invändig diameter: 1.510 mm

Mått utlopp till marken: 270 mm

Total höjd: 1.300 mm

Ytterdiameter: 1.600 mm

## Värmeväxlare

Typ av värmeväxlare på cylinder: dimple-jacket

Typ av värmeväxlare på botten: dimple-jacket

Vattentryck värmeväxlare: 3 Bar

Vattentryck värmeväxlare botten: 3 Bar

## Mer

Värmeväxlare: RVS 304

Isolerad: Ja