

## 1000 liter tank i Syrafast 316



**64,000,00 kr /st exkl moms**

**Additional information:** Dairy; Diameter manhole approx. 420 mm; Insulation around the cylinder (small dents in the insulation jacket)

**Volumetric volume (L):** 1.000 L

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 90 °C  
**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical  
**Configuration:** insulated  
**Heat exchanger:** no  
**Insulation:** yes  
**Mobile tank:** no

**Total discharge:** yes  
**Documents included:** no  
**Technical drawing included:** no  
**Registration plate on the tank:** no  
**Flange for agitator:** no

**Position of manway:** headside  
**Outlet of tank:** 65  
**Agitator:** yes  
**Number of revolutions:** 56  
**Power:** 0,75

**Internal diameter tank:** 990 mm  
**Outer diameter tank:** 1.120 mm  
**Cylinder height:** 1.430 mm  
**Total height of tank:** 3.100 mm

**SKU:** 456536

Mer information



## Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Max. arbetstemperatur: 90 °C

Mobil tank: Nej

Övrig information: Dairy; Diameter manhole approx. 420 mm; Insulation around the cylinder (small dents in the insulation jacket); we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1000

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.430 mm

Invändig diameter: 990 mm

Total höjd: 3.100 mm

Ytterdiameter: 1.120 mm

## Omrörare

Kraft (kW): 0,75

Varvtal: 56

**Mer**

Isolerad: Ja

---