

1000 liter tank i Syrafast 316



63 000 SEK /st exkl moms

Additional information: Dairy; Manhole diameter approx. 420 mm; insulation around the cylinder (small dents in the insulating jacket)

Volumetric volume (L): 1.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 90 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Position of manway: headside
Outlet of tank: 65
Agitator: yes
Number of revolutions: 56
Power: 0,75

Internal diameter tank: 990 mm
Outer diameter tank: 1.120 mm
Cylinder height: 1.430 mm
Total height of tank: 3.100 mm

SKU: 456536

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfäric

Konfiguration: insulated

Max. arbetstemperatur: 90 °C

Mobil tank: Nej

Övrig information: Dairy; Diameter manhole approx. 420 mm; Insulation around the cylinder (small dents in the insulation jacket); we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.430 mm

Invändig diameter: 990 mm

Total höjd: 3.100 mm

Ytterdiameter: 1.120 mm

Omrörare

Kraft (kW): 0,75

Varvtal: 56

Mer

Isolerad: Ja
