1000 liter tank i Syrafast 316



64 000 SEK /st exkl moms

Additional information: Manhole diameter approx. 420 mm; insulation around the cylinder (small dents in the insulating jacket)
Volumetric volume (L): 1.000 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 90 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Position of manway: headside
Outlet of tank: 65
Agitator: yes
Number of revolutions: 56
Power: 0,75

Internal diameter tank: 990 mm
Outer diameter tank: 1.120 mm
Cylinder height: 1.430 mm
Total height of tank: 3.100 mm

SKU: 456536

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated
Max. arbetstemperatur: 90 °C
Mobil tank: Nej
Övrig information: Dairy; Diameter manhole approx. 420 mm; Insulation around the cylinder (small dents in the insulation jacket); we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.430 mm
Invändig diameter: 990 mm
Total höjd: 3.100 mm
Ytterdiameter: 1.120 mm

Omrörare

Kraft (kW): 0,75
Varvtal: 56

Mer
Isolerad: Ja