

## 1000 liter tank i Syrafast 316



**77 000 SEK /st exkl moms**

**Additional information:** Confectionery industry; Accessible frame, Aisi 304 with 4 height-adjustable feet; 2 impact protection rings, Aisi 304 on the outside of the cylinder; Manhole approx. 305 x 440 mm; Slight corrosion in the area of 1 connection (see interior photos); some residues of previous content; traces of usage



**Volumetric volume (L):** 1.000 L  
**Pressure in tank:** ATM - atmosferic  
**Max. temperature (°C):** 80 °C  
**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical  
**Configuration:** insulated with heat-exchanger  
**Heat exchanger:** yes  
**Insulation:** yes  
**Mobile tank:** no

**Total discharge:** yes  
**Max Overpressure:** 3 Bar  
**Max. working temperature:** 80 °C  
**Documents included:** no  
**Technical drawing included:** no

**Registration plate on the tank:** yes  
**Flange for agitator:** no  
**Position of manway:** in the bottom  
**Outlet of tank:** DN65 DIN 11851  
**Agitator:** yes

**Number of revolutions:** 15  
**Power:** 1,50  
**Internal diameter tank:** 1.090 mm  
**Outer diameter tank:** 1.200 mm  
**Cylinder height:** 1.000 mm

**Total height of tank:** 1.950 mm

**SKU:** 287198

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfäric

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 80 °C

Mobil tank: Nej

Övrig information: Confectionery industry; Accessible frame, Aisi 304 with 4 height-adjustable feet; 2 impact protection rings, Aisi 304 on the outside of the cylinder; Manhole approx. 305 x 440 mm; Slight corrosion

Övrig information2:

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1000

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## Dimensioner av tank

Cylinderhöjd: 1.000 mm  
Invändig diameter: 1.090 mm  
Total höjd: 1.950 mm  
Ytterdiameter: 1.200 mm

## Omrörare

Kraft (kW): 1,50  
Varvtal: 15

## Mer

Isolerad: Ja