1000 liter tank i Syrafast 316



185 000 SEK /st exkl moms

Additional information: Pharmacy; Double jacket with trickle ring (entry only possible via the upper heating/cooling connection); a combination of height-adjustable foot screw/load cell on the tank (see photo; no guarantee of functionality; was not taken into account when specifying the total height); some residues of previous content
Volumetric volume (L): 1.000 L

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 145 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single jacketed with heat-exchanger
Heat exchanger: yes

Insulation: no
Mobile tank: no
Total discharge: yes
Max Overpressure: 3 Bar
Max onderdruk: 1 Bar

Max. working temperature: 60 °C
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: 25
Agitator: yes
Number of revolutions: 935

Power: 1,50
Top: 5,10 mm
Cylinder: 5 mm
Bottom: 4,20 mm
Internal diameter tank: 1.400 mm

Outer diameter tank: 1.515 mm
Cylinder height: 500 mm
Total height of tank: 2.100 mm

SKU: 412292

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 145 °C
Mobil tank: Nej
Övrig information: Pharmacy; Double jacket with trickle ring (entry only possible via the upper heating/cooling connection); a combination of height-adjustable foot screw/load cell on the tank (see photo; no guarantee
Övrig information2: of functionality; was not taken into account when specifying the total height) ; some residues of previous content; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material
Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 500 mm
Invändig diameter: 1.400 mm
Total höjd: 2.100 mm
Ytterdiameter: 1.515 mm

Omrörare
Kraft (kW): 1,50
Varvtal: 935

Tjocklek på tank
Botten: 4,20 mm
Cylinder: 5 mm
Topp: 5,10 mm

Mer
Isolerad: Nej

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se