

1000 liter tank i Syrafast 316



185,000,00 kr /st exkl moms

Additional information: Pharmacy; Double jacket with trickle ring (entry only possible via the upper heating/cooling connection); a combination of height-adjustable foot screw/load cell on the tank (see photo; no guarantee of functionality; was not taken into account when specifying the total height); some residues of previous content

Volumetric volume (L): 1.000 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 145 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Max Overpressure: 3 Bar

Max onderdruk: 1 Bar

Max. working temperature: 60 °C

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 25

Agitator: yes

Number of revolutions: 935

Power: 1,50

Top: 5,10 mm

Cylinder: 5 mm

Bottom: 4,20 mm

Internal diameter tank: 1.400 mm

Outer diameter tank: 1.515 mm

Cylinder height: 500 mm

Total height of tank: 2.100 mm

SKU: 288731

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 145 °C

Mobil tank: Nej

Övrig information: Pharmacy; Double jacket with trickle ring (entry only possible via the upper heating/cooling connection); a combination of height-adjustable foot screw/load cell on the tank (see photo; no guarantee

Övrig information2: of functionality; was not taken into account when specifying the total height) ; some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1000



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 500 mm
Invändig diameter: 1.400 mm
Total höjd: 2.100 mm
Ytterdiameter: 1.515 mm

Omrörare

Kraft (kW): 1,50
Varvtal: 935

Tjocklek på tank

Botten: 4,20 mm
Cylinder: 5 mm
Topp: 5,10 mm

Mer

Isolerad: Nej