1000 liter tank i Syrafast 316



113 000 SEK /st exkl moms

Additional information: Pharmacy; Hand hole diameter approx. 265 mm; Attention: The information on the operating pressure of the tank and double jacket as well as the maximum operating temperature of the tank was taken from a drawing that can be assigned to one of the two identical tanks using the inventory number; only one drawing is available, but it should also apply to the second tank; dents at the insulation jacket

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Volumetric volume (L): 1.000 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 1,80 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Max Overpressure: 2 Bar
Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Outlet of tank: 48
Top: 5 mm
Cylinder: 6 mm
Bottom: 6 mm
Internal diameter tank: 1.138 mm

Outer diameter tank: 1.290 mm
Total height of tank: 2.200 mm

SKU: 421871

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 130 °C
Mobil tank: Nej
Övrig information: Pharmacy; Hand hole diameter approx. 265 mm; Attention: The information on the operating pressure of the tank and double jacket as well as the maximum operating temperature of the tank was taken
Övrig information2:
Omrörare: Nej
Övertryck: 1,80 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Invändig diameter: 1.138 mm
Total höjd: 2.200 mm
Ytterdiameter: 1.290 mm

Tjocklek på tank
Botten: 6 mm
Cylinder: 6 mm
Topp: 5 mm

Mer
Isolerad: Ja