

1000 liter tank i Syrafast 316



57,000,00 kr /st exkl moms

Additional information: chemistry; vessel flange made of mild steel; handholecover clad

Volumetric volume (L): 1.000 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 0,50 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 143 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 80 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 149 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 85

Agitator: yes

Number of revolutions: 48.5 / 97

Power: 4.5 / 5.5

Top: 5,10 mm

Cylinder: 3,90 mm

Bottom: 5,30 mm

Internal diameter tank: 1.200 mm

Cylinder height: 850 mm

Total height of tank: 3.750 mm

SKU: 267064

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 143 °C

Mobil tank: Nej

Övrig information: chemistry; vessel flange made of mild steel; handholecover clad; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 0,50 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 850 mm
Invändig diameter: 1.200 mm
Total höjd: 3.750 mm

Omrörare

Kraft (kW): 4.5 / 5.5
Varvtal: 48.5 / 97

Tjocklek på tank

Botten: 5,30 mm
Cylinder: 3,90 mm
Topp: 5,10 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Nej