1000 liter tank i Syrafast 316



213 000 SEK /st exkl moms

Additional information: Double jacket must be operated without pressure; 2 electric heaters (6 kW) for heating the heating medium in the double jacket; Attention: The vessel is delivered without heating medium (glycerine or thermal oil), which must be filled in on site before commissioning; switch cabinet for the electric heaters available (temperature of the double jacket can be regulated via switch cabinet); 2 ball valves for the heating jacket are included in the scope of delivery; contrary to the information in the drawing, the inside of

the vessel is not polished
Volumetric volume (L): 1.000 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 90 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: DN50 DIN 11851
Agitator: yes
Number of revolutions: 0 - 1400

Power: 0,75
Cylinder: 2 mm
Bottom: 2 mm
Internal diameter tank: 1.150 mm
Outer diameter tank: 1.250 mm

Cylinder height: 1.000 mm
Total height of tank: 1.900 mm
Empty weight tank: 700

SKU: 415205

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 90 °C
Mobil tank: Nej
Övrig information: Double jacket must be operated without pressure; 2 electric heaters (6 kW) for heating up the heating medium in the double jacket; Attention: The tank is delivered without heating medium (glycerine
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.000 mm
Invändig diameter: 1.150 mm
Total höjd: 1.900 mm
Ytterdiameter: 1.250 mm

Omrörare
Kraft (kW): 0,75
Varvtal: 0 – 1400

Tjocklek på tank
Botten: 2 mm
Cylinder: 2 mm

Mer
Isolerad: Ja
Vikt: 700