1000 liter tank i Syrafast 316



18 000 SEK /st exkl moms

Additional information: Diameter manhole approx. 385 mm; 2 stronger dents in the transition of the cylinder to the floors; slight corrosion inside the container
Volumetric volume (L): 1.000 L
Pressure in tank: pressure
Max. pressure (Bar): 0,49 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 0,49 Bar

Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Position of manway: headside
Outlet of tank: 48
Top: 2,50 mm
Cylinder: 2,50 mm

Bottom: 2,40 mm
Internal diameter tank: 1.190 mm
Cylinder height: 730 mm
Total height of tank: 2.000 mm

SKU: 476527

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: Pharmazie; Durchmesser Mannloch ca. 385 mm; 2 stärkere Beulen im Übergang des Zylinders zu den Böden; leichter Korrosionsansatz im Inneren des Containers
Omrörare: Nej
Övertryck: 0,49 Bar
Total urtappning: Ja
Undertryck (vakuum): 0,49 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 730 mm
Invändig diameter: 1.190 mm
Total höjd: 2.000 mm

Tjocklek på tank
Botten: 2,40 mm
Cylinder: 2,50 mm
Topp: 2,50 mm

Mer
Isolerad: Nej