

## 1000 liter tank i Syrafast 316



**63 000 SEK /st exkl moms**

item available on order

**Article type:** second-hand storage tank - type K-HL

**Additional information:** Never been used

**Volumetric volume (L):** 1.000 L

**Max. density P (kg/m<sup>3</sup>):** 1.200

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Top type:** conical 15 °

**Shape of tank:** cylindrical

**Bottom type:** conical 15 °

**Total discharge:** yes

**Fixation points:** 3 adjustable feet

**Legs:** Set of baseplates and adjusting pieces included

**Type of HE on the cylinder:** half pipe welded onto the outside of the innertank

**Position HE:** the middle part of the cilinder

**Number of windings:** 4

**Height HE:** 860 mm

**Number of sections:** 1

**Water pressure HE:** 2,50 Bar

**Steam pressure HE:** 1 Bar

**Contact surface cylinder:** 1,30 m<sup>2</sup>

**Connection HE:** 1" BSP

**Working temperature HE cylinder:** 100 °C

**Type HE:** half pipe welded onto the outside of the innertank

**Heat exchanger:** RVS 304

**Manway(s):** RVS 316

**Gasket manway(s):** parra rubber

**Valve:** RVS 316L

**Fixation point(s):** RVS 304

**Suitable for food industry:** yes

**Documents included:** yes, optional

**Technical drawing included:** yes

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** at the top

**Height manhole 1 (mm):** 400 mm

**Hinged lid:** yes

**CIP spray ball:** no

**Tank outlet:** inside Ø 50 mm

**Outlet type:** DIN11851

**Total outlet valve:** no, optional

**Adjustable legs:** yes

**Agitator:** no, optional

**Top:** 2,50 mm

**Cylinder:** 2 mm

**Bottom:** 2,50 mm

**Internal diameter tank:** 908 mm

**Distance from outlet to ground:** 300 mm

**Outer diameter tank:** 978 mm

**Cylinder height:** 1.500 mm

**Feet height:** 472 mm

**Total height of tank:** 2.250 mm

**Empty weight tank:** 135

**SKU:** 435602

## Mer information



## Beskrivning av produkt

Livsmedelsklassad: Ja  
Material: Syrafast 316  
Modell: Vertikal  
Nyttillverkad/Begagnad: Begagnad  
Arbetsstryck i tank: ATM – atmosferic  
Konfiguration: single jacketed with heat-exchanger  
Maximal densitet för produkten: 1200  
Mobil tank: Nej  
Övrig information: Never been used  
Omrörare: Nej  
Tankens form: cylindrical  
Total urtappning: Ja  
Typ av botten: conical 15 °  
Uppvärmning/kylning: Ja  
Vätskeberörd yta: SS AISI 316 (V4A)  
Volym i liter: 1000

## Utrustning

Fläns för omrörare: Nej  
Märkskylt: Ja  
Livsmedelsklassad: Ja  
Tankutlopp: inside Ø 50 mm  
Teknisk ritning finns: Ja  
Utloppstyp: DIN11851

## Översikt material

Material: Syrafast 316  
Fixeringspunkt(er): RVS 304

## Dimensioner av tank

Cylinderhöjd: 1.500 mm  
Höjd på fötter: 472 mm  
Invändig diameter: 908 mm  
Mått utlopp till marken: 300 mm  
Total höjd: 2.250 mm  
Ytterdiameter: 978 mm

## Värmeväxlare

Ångtryck värmeväxlare: 1 Bar  
Anslutning värmeväxlare: 1" BSP  
Arbetstemperatur värmeväxlare cylinder: 100 °C  
Höjd värmeväxlare: 860 mm  
Kontaktyta cylinder: 1,30 m<sup>2</sup>  
Position värmeväxlare: the middle part of the cilinder  
Typ av värmeväxlare på cylinder: half pipe welded onto the outside of the innertank  
Vattentryck värmeväxlare: 2,50 Bar

## Tjocklek på tank

Botten: 2,50 mm  
Cylinder: 2 mm  
Topp: 2,50 mm

## Mer

Värmeväxlare: RVS 304  
Isolerad: Nej  
Vikt: 135