

1000 liter tank i Syrafast 316



212,000,00 kr /st exkl moms

Additional information: Double jacket must be operated without pressure; 2 electric heaters (6 kW) for heating up the heating medium in the double jacket; Attention: The tank is delivered without heating medium (glycerine or thermal oil), which must be filled in on site before commissioning; control cabinet for the electric heaters available (temperature of the double jacket can be regulated via the control cabinet); 2

ball valves for the heating jacket are included in the scope of delivery.

Volumetric volume (L): 1.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 90 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 0 - 1400

Power: 0,75

Cylinder: 2 mm

Bottom: 2 mm

Internal diameter tank: 1.150 mm

Outer diameter tank: 1.250 mm

Cylinder height: 1.000 mm

Total height of tank: 1.900 mm

Empty weight tank: 700

SKU: 436304

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfäric

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 90 °C

Mobil tank: Nej

Övrig information: Double jacket must be operated without pressure; 2 electric heaters (6 kW) for heating up the heating medium in the double jacket; This heating medium (glycerin or thermal oil) would have to be

Övrig information2:

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.000 mm
Invändig diameter: 1.146 mm
Total höjd: 1.880 mm
Ytterdiameter: 1.250 mm

Omrörare

Kraft (kW): 0,75
Varvtal: 0 – 1400

Tjocklek på tank

Botten: 2 mm
Cylinder: 2 mm

Mer

Isolerad: Ja
Vikt: 700