1000 liter tank i Syrafast 316



71 000 SEK /st exkl moms

Additional information: 1 Screw connection of the manhole cover damaged
Volumetric volume (L): 1.000 L
Pressure in tank: pressure
Max. pressure (Bar): 2 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 2 Bar

Max. temperature (°C): 120 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 97 L
Max Overpressure: 2 Bar

Max. working temperature: 134 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: available
Internal diameter tank: 1.180 mm

Outer diameter tank: 1.360 mm
Total height of tank: 1.950 mm

SKU: 486017

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 120 °C
Mobil tank: Nej
Övrig information: Pharmacy; 1 screw connection of the manhole cover damaged; we can’t give any guarantees about the heating/cooling jacket
Omrörare: Nej
Övertryck: 2 Bar
Total urtappning: Ja
Undertryck (vakuum): 2 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 1.180 mm
Total höjd: 1.950 mm
Ytterdiameter: 1.360 mm

Mer
Isolerad: Ja