1000 liter tank i Syrafast 316



100 000 SEK /st exkl moms

Additional information: Fermenter in a biotechnology company; 1 aeration pipe inside the vessel; outlet reduced to an internal diameter of approx. 19 mm by several fittings; mobile stainless steel 304 frame
Volumetric volume (L): 1.000 L
Pressure in tank: ATM - atmosferic
Max. pressure (Bar): 4 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single jacketed with heat-exchanger
Heat exchanger: yes

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 64 L
Max Overpressure: 3,50 Bar

Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: available
Number of revolutions: 389
Power: 7,50

Internal diameter tank: 1.200 mm
Outer diameter tank: 1.250 mm
Total height of tank: 2.850 mm
Total outer width: 1.900 mm
Total outer length: 1.700 mm

Empty weight tank: 700

SKU: 490491

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: Fermenter in a biotechnology company; 1 aeration pipe inside the vessel; outlet reduced to an internal diameter of approx. 19 mm by several fittings; mobile stainless steel 304 frame
Omrörare: Nej
Övertryck: 4 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Dimensioner av tank
Invändig diameter: 1.200 mm
Total höjd: 2.850 mm
Ytterdiameter: 1.250 mm

Omrörare
Kraft (kW): 7,50
Varvtal: 389

Mer
Isolerad: Nej
Vikt: 700