

1000 liter tank i Syrafast 316



99 000 SEK /st exkl moms

Additional information: Fermenter in a biotechnology company; 1 aeration pipe inside the vessel; outlet reduced to an internal diameter of approx. 19 mm by several fittings; mobile stainless steel 304 frame

Volumetric volume (L): 1.000 L

Pressure in tank: ATM - atmosferic

Max. pressure (Bar): 4 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 64 L

Max Overpressure: 3,50 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: available

Number of revolutions: 389

Power: 7,50

Internal diameter tank: 1.200 mm

Outer diameter tank: 1.250 mm

Total height of tank: 2.850 mm

Total outer width: 1.900 mm

Total outer length: 1.700 mm

Empty weight tank: 700

SKU: 490491

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Fermenter in a biotechnology company; 1 aeration pipe inside the vessel; outlet reduced to an internal diameter of approx. 19 mm by several fittings; mobile stainless steel 304 frame

Omrörare: Nej

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Invändig diameter: 1.200 mm

Total höjd: 2.850 mm

Ytterdiameter: 1.250 mm

Omrörare

Kraft (kW): 7,50

Varvtal: 389

Mer

Isolerad: Nej

Vikt: 700