

## 1000 liter tank i Syrafast 316



**37,000,00 kr /st exkl moms**

**Additional information:** Biochemistry; Manhole diameter approx. 420 mm; some residues of previous content; manhole cover plated

**Volumetric volume (L):** 1.000 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 2 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** 53

**Top:** 8,10 mm

**Cylinder:** 5 mm

**Bottom:** 6,70 mm

**Internal diameter tank:** 1.190 mm

**Cylinder height:** 950 mm

**Total height of tank:** 2.550 mm

**SKU:** 564913

Mer information

## Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Biochemistry; Manhole diameter approx. 420 mm; some residues of previous content; manhole cover plated

Omrörare: Nej

Övertryck: 2 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1000

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 950 mm

Invändig diameter: 1.190 mm

Total höjd: 2.550 mm

**Tjocklek på tank**

Botten: 6,70 mm

Cylinder: 5 mm

Topp: 8,10 mm

**Mer**

Isolerad: Nej