

## 1000 liter tank i Syrafast 316



**214,000,00 kr /st exkl moms**

**Additional information:** Double jacket must be operated without pressure; 2 electric heaters (6 kW) for heating up the heating medium in the double jacket; Attention: The tank is delivered without heating medium (glycerine or thermal oil), which must be filled in on site before commissioning; control cabinet for the electric heaters available (temperature of the double jacket can be regulated via the control cabinet); 2

ball valves for the heating jacket are included in the scope of delivery.

**Volumetric volume (L):** 1.000 L

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 90 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** DN50 DIN 11851

**Agitator:** yes

**Number of revolutions:** 0 - 1400

**Power:** 0,75

**Cylinder:** 2 mm

**Bottom:** 2 mm

**Internal diameter tank:** 1.150 mm

**Outer diameter tank:** 1.250 mm

**Cylinder height:** 1.000 mm

**Total height of tank:** 1.900 mm

**Empty weight tank:** 700

**SKU:** 451367

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfäric

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 90 °C

Mobil tank: Nej

Övrig information: Double jacket must be operated without pressure; 2 electric heaters (6 kW) for heating up the heating medium in the double jacket; Attention: The tank is delivered without heating medium (glycerine)

Övrig information2:

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1000

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## **Dimensioner av tank**

Cylinderhöjd: 1.000 mm  
Invändig diameter: 1.150 mm  
Total höjd: 1.900 mm  
Ytterdiameter: 1.250 mm

## **Omrörare**

Kraft (kW): 0,75  
Varvtal: 0 – 1400

## **Tjocklek på tank**

Botten: 2 mm  
Cylinder: 2 mm

## **Mer**

Isolerad: Ja  
Vikt: 700