10000 liter tank i GAP/Plast



142 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: The tanks have never been used, only for test runs; we can't give any guarantees about the agitator
Volumetric volume (L): 10.000 L
Max. density P (kg/m³): 1.180
Pressure in tank: ATM - atmosferic

Max. temperature (°C): 95 °C
Material wet parts: polyester (fiberglass)
Model: vertical
Configuration: single-skin

Heat exchanger: no

Insulation: no
Mobile tank: no
Top type: dished
Shape of tank: cylindrical
Bottom type: dished

Total discharge: yes
Fixation points: on skirt
Manway(s): polyester
Fixation point(s): polyester
Suitable for food industry: no

Documents included: yes, optional
Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1

Position of manway: cylinder
Height manhole 1 (mm): 600 mm
Agitator: yes
Agitator type: propeller agitator
Position engine: at the top

Number of revolutions: 45
Power: 1,10
Voltage: three-phase
Internal diameter tank: 2.000 mm
Outer diameter tank: 2.120 mm

Total height of tank: 3.788 mm
Empty weight tank: 1.040

SKU: 486665

Mer information

Beskrivning av produkt

Material: GAP/Plast
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: single-skin
Max. arbetstemperatur: 95 °C
Maximal densitet för produkten: 1180
Mobil tank: Nej
Övrig information: The tanks have never been used, only for test runs; we can't give any guarantees about the agitator
Omrörare: Ja
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: dished
Uppvärmning/kylning: Nej
Vätskeberörd yta: polyester (fiberglass)
Volym i liter: 10000

Utrustning

Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Ja

Översikt material

Material: GAP/Plast
Fixeringspunkt(er): polyester

Dimensioner av tank
Invändig diameter: 2.000 mm
Total höjd: 3.788 mm
Ytterdiameter: 2.120 mm

Omrörare
Kraft (kW): 1,10
Position motor: at the top
Typ av omrörare: propeller agitator
Varvtal: 45
Spänning (Volt): three-phase

Mer
Isolerad: Nej
Vikt: 1.040