

## 10000 liter tank i GAP/Plast



**139,000,00 kr /st exkl moms**

**Article type:** second-hand mixing tank

**Additional information:** The tanks have never been used, only for test runs; we can't give any guarantees about the agitator

**Volumetric volume (L):** 10.000 L

**Max. density P (kg/m<sup>3</sup>):** 1.180

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 95 °C

**Material wet parts:** polyester (fiberglass)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Top type:** dished

**Shape of tank:** cylindrical

**Bottom type:** dished

**Total discharge:** yes

**Fixation points:** on skirt

**Manway(s):** polyester

**Fixation point(s):** polyester

**Suitable for food industry:** no

**Documents included:** yes, optional

**Technical drawing included:** yes

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** cylinder

**Height manhole 1 (mm):** 600 mm

**Agitator:** yes

**Agitator type:** propeller agitator

**Position engine:** at the top

**Number of revolutions:** 45

**Power:** 1,10

**Voltage:** three-phase

**Internal diameter tank:** 2.000 mm

**Outer diameter tank:** 2.120 mm

**Total height of tank:** 3.788 mm

**Empty weight tank:** 1.040

**SKU:** 486665

## Mer information

### Beskrivning av produkt

Material: GAP/Plast

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Max. arbetstemperatur: 95 °C

Maximal densitet för produkten: 1180

Mobil tank: Nej

Övrig information: The tanks have never been used, only for test runs; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: dished

Uppvärmning/kylning: Nej

Vätskeberörd yta: polyester (fiberglass)

Volym i liter: 10000

### Utrustning

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Ja

### Översikt material

Material: GAP/Plast

Fixeringspunkt(er): polyester

## Dimensioner av tank

Invändig diameter: 2.000 mm

Total höjd: 3.788 mm

Ytterdiameter: 2.120 mm

## Omrörare

Kraft (kW): 1,10

Position motor: at the top

Typ av omrörare: propeller agitator

Varvtal: 45

Spänning (Volt): three-phase

## Mer

Isolerad: Nej

Vikt: 1.040