

10000 liter tank i GAP/Plast



139,000,00 kr /st exkl moms

Article type: second-hand mixing tank

Additional information: The tanks have never been used, only for test runs; we can't give any guarantees about the agitator

Volumetric volume (L): 10.000 L

Max. density P (kg/m³): 1.180

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 95 °C

Material wet parts: polyester (fiberglass)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Total discharge: yes

Fixation points: on skirt

Manway(s): polyester

Fixation point(s): polyester

Suitable for food industry: no

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: cylinder

Height manhole 1 (mm): 600 mm

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Number of revolutions: 45

Power: 1,10

Voltage: three-phase

Internal diameter tank: 2.000 mm

Outer diameter tank: 2.120 mm

Total height of tank: 3.788 mm

Empty weight tank: 1.040

SKU: 486665

Mer information

Beskrivning av produkt

Material: GAP/Plast

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Max. arbetstemperatur: 95 °C

Maximal densitet för produkten: 1180

Mobil tank: Nej

Övrig information: The tanks have never been used, only for test runs; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: dished

Uppvärmning/kylning: Nej

Vätskeberörd yta: polyester (fiberglass)

Volym i liter: 10000

Utrustning

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Ja

Översikt material

Material: GAP/Plast

Fixeringspunkt(er): polyester

Dimensioner av tank

Invändig diameter: 2.000 mm

Total höjd: 3.788 mm

Ytterdiameter: 2.120 mm

Omrörare

Kraft (kW): 1,10

Position motor: at the top

Typ av omrörare: propeller agitator

Varvtal: 45

Spänning (Volt): three-phase

Mer

Isolerad: Nej

Vikt: 1.040