10000 liter tank i Rostfritt 304



82 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: Please look carefully at the photos, In 2 of the 3 tanks there is still some grease on the inner wall
.; we can't give any guarantees about the agitator
Volumetric volume (L): 10.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: single-skin
Heat exchanger: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Insulation: no
Mobile tank: no

Shape of tank: cylindrical
Bottom type: dished
Total discharge: yes
Fixation points: 4 non adjustable feet
Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)
Suitable for food industry: no
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Tank outlet: inside Ø 80 mm
Agitator: yes
Cylinder: 3 mm
Bottom: 4 mm

Internal diameter tank: 1.920 mm
Distance from outlet to ground: 700 mm
Outer diameter tank: 2.020 mm
Cylinder height: 3.540 mm
Total height of tank: 5.600 mm

Empty weight tank: 1.250

SKU: 427994

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: Please look carefully at the photos, In 2 of the 3 tanks there is still some grease on the inner wall .; we can’t give any guarantees about the agitator
Omrörare: Ja
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: dished
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 10000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Tankutlopp: inside Ø 80 mm
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Dimensioner av tank

Cylinderhöjd: 3.540 mm
Invändig diameter: 1.920 mm
Mått utlopp till marken: 700 mm
Total höjd: 5.600 mm
Ytterdiameter: 2.020 mm

Tjocklek på tank

Botten: 4 mm
Cylinder: 3 mm

Mer

Isolerad: Nej
Vikt: 1.250

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se