

## 10000 liter tank i Rostfritt 304



**259 000 SEK /st exkl moms**

**Additional information:** Ice water; Manhole approx. 410 x 510 mm; heating connections cut off; 3 identical tanks (motor/gear unit missing) also available (#B0218)

**Volumetric volume (L):** 10.000 L

**Pressure in tank:** ATM - atmosferic



**Max. temperature (°C):** 10 °C

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 205 L

**Max Overpressure:** 3 Bar

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** cylinder

**Outlet of tank:** DN50 DIN 11851

**Agitator:** yes

**Number of revolutions:** 17 / 35

**Power:** 1.2 / 2.2

**Cylinder:** 4 mm

**Bottom:** 4 mm

**Internal diameter tank:** 1.660 mm

**Outer diameter tank:** 1.790 mm

**Cylinder height:** 4.500 mm

**Total height of tank:** 6.600 mm

**SKU:** 457631

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 10 °C

Mobil tank: Nej

Övrig information: Ice water; Manhole appr. 410 x 510 mm; Heating connections cut off; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Övrig information2: jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 10000

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Rostfritt 304

## Dimensioner av tank

Cylinderhöjd: 4.500 mm  
Invändig diameter: 1.660 mm  
Total höjd: 6.600 mm  
Ytterdiameter: 1.790 mm

## Omrörare

Kraft (kW): 1.2 / 2.2  
Varvtal: 17 / 35

## Tjocklek på tank

Botten: 4 mm  
Cylinder: 4 mm

## Mer

Isolerad: Ja