10000 liter tank i Rostfritt 304

94,000,00 kr /st exkl moms

Additional information: seal manufacturing; insulation jacket with dents and metal cutoffs; 1 bent connection in the upper bottom; slight metallic discolourations inside; some residues of previous content
Volumetric volume (L): 10.000 L
Pressure in tank: ATM - atmosferic

Max. temperature (°C): 80 °C
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no

Total discharge: yes
Max Overpressure: 2 Bar
Max. working temperature: 80 °C
Heat exchanger: RVS 304
Documents included: no

Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Position of manway: headside
Outlet of tank: available

Agitator: yes
Number of revolutions: 55 - 136
Power: 5
Internal diameter tank: 2.390 mm
Outer diameter tank: 2.640 mm

Cylinder height: 2.000 mm
Total height of tank: 4.550 mm

SKU: 272479

Mer information

Beskrivning av produkt
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 80 °C
Mobil tank: Nej
Övrig information: seal manufacturing; insulation jacket with dents and metal cutoffs; 1 bent connection in the upper bottom; slight metallic discolourations inside; some residues of previous content; we can't give
Övrig information2: any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 10000

Utrustning
Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material
Material: Rostfritt 304

Dimensioner av tank
Cylinderhöjd: 2.000 mm
Invändig diameter: 2.390 mm
Total höjd: 4.550 mm
Ytterdiameter: 2.640 mm

Omrörare
Kraft (kW): 5
Varvtal: 55 – 136

Mer
Värmeväxlare: RVS 304
Isolerad: Ja