10000 liter tank i Rostfritt 304



56 000 SEK /st exkl moms

Additional information: dairy; manhole diameter approx. 520 mm; feet: upper part made of stainless steel, lower part and height-adjustable screws made of Fe; one of the feet has come loose and would have to be welded again on site before the container will be installed; some residues of previous content; bump at the insulation jacket
Volumetric volume (L): 10.000 L

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: no

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Position of manway: headside

Outlet of tank: 50
Number of revolutions: 700
Power: 3
Internal diameter tank: 2.180 mm
Outer diameter tank: 2.400 mm

Cylinder height: 2.460 mm
Total height of tank: 4.600 mm

SKU: 396692

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: dairy; manhole diameter approx. 520 mm; feet: upper part made of stainless steel, lower part and height-adjustable screws made of Fe; one of the feet has come loose and would have to be welded again
Övrig information2: on site before the container will be installed; some residues of previous content;bump at the insulation jacket
Omrörare: Nej
Total urtappning: Nej
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 10000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 2.460 mm
Invändig diameter: 2.180 mm
Total höjd: 4.600 mm
Ytterdiameter: 2.400 mm

Omrörare
Kraft (kW): 3
Varvtal: 700

Mer
Isolerad: Nej