

10000 liter tank i Syrafast 316



133,000,00 kr /st exkl moms

Additional information: Slurry; Type plate no longer available; further technical documents available; Diameter manhole cylinder 600 mm; a taper DN 50 is flanged to the outlet; 1 additional container of the same design is available on request

Volumetric volume (L): 10.000 L

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Outlet of tank: flange DN80
Cylinder: 3 mm
Bottom: 4 mm
Internal diameter tank: 2.500 mm
Cylinder height: 1.500 mm

Total height of tank: 3.600 mm

SKU: N/A

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Max. arbetstemperatur: 80 °C

Mobil tank: Nej

Övrig information: Slurry; Type plate no longer available; further technical documents available; Diameter manhole cylinder 600 mm; a taper DN 50 is flanged to the outlet; 1 additional container of the same design is

Övrig information2: available on request

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 10000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.500 mm

Invändig diameter: 2.500 mm

Total höjd: 3.600 mm

Tjocklek på tank

Botten: 4 mm

Cylinder: 3 mm

Mer

Isolerad: Nej