

## 10000 liter tank i Syrafast 316



**129,000,00 kr /st exkl moms**

**Additional information:** Slurry; Type plate no longer available; further technical documents available; Diameter manhole cylinder 600 mm; a taper DN 50 is flanged to the outlet; 1 additional container of the same design is available on request

**Volumetric volume (L):** 10.000 L

**Pressure in tank:** ATM - atmosferic  
**Max. temperature (°C):** 80 °C  
**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical  
**Configuration:** single-skin  
**Heat exchanger:** no  
**Insulation:** no  
**Mobile tank:** no

**Total discharge:** yes  
**Documents included:** no  
**Technical drawing included:** no  
**Registration plate on the tank:** no  
**Flange for agitator:** no

**Outlet of tank:** flange DN80  
**Cylinder:** 3 mm  
**Bottom:** 4 mm  
**Internal diameter tank:** 2.500 mm  
**Cylinder height:** 1.500 mm

**Total height of tank:** 3.600 mm

**SKU:** N/A

Mer information

## Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Max. arbetstemperatur: 80 °C

Mobil tank: Nej

Övrig information: Slurry; Type plate no longer available; further technical documents available; Diameter manhole cylinder 600 mm; a taper DN 50 is flanged to the outlet; 1 additional container of the same design is

Övrig information2: available on request

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 10000

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.500 mm

Invändig diameter: 2.500 mm

Total höjd: 3.600 mm

**Tjocklek på tank**

Botten: 4 mm

Cylinder: 3 mm

**Mer**

Isolerad: Nej