

10000 liter tank i Syrafast 316



199,000 SEK /st exkl moms

Additional information: 1 rectangular opening approx. 400 x 720 mm in the folding segment

Volumetric volume (L): 10.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 98 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 120 L

Max Overpressure: 3 Bar

Max. working temperature: 120 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN65 DIN 11851

Agitator: yes

Internal diameter tank: 2.500 mm

Outer diameter tank: 2.640 mm

Cylinder height: 1.990 mm

Total height of tank: 4.350 mm

SKU: 281809

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 98 °C

Mobil tank: Nej

Övrig information: 1 rectangular opening approx. 400 x 720 mm in the folding segment; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 10000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.990 mm

Invändig diameter: 2.500 mm

Total höjd: 4.350 mm

Ytterdiameter: 2.640 mm

Mer

Isolerad: Ja
