

## 10000 liter tank i Syrafast 316



**202,000,00 kr /st exkl moms**

**Additional information:** 1 rectangular opening approx. 400 x 720 mm in the folding segment

**Volumetric volume (L):** 10.000 L

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 98 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 120 L

**Max Overpressure:** 3 Bar

**Max. working temperature:** 120 °C

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** DN65 DIN 11851

**Agitator:** yes

**Internal diameter tank:** 2.500 mm

**Outer diameter tank:** 2.640 mm

**Cylinder height:** 1.990 mm

**Total height of tank:** 4.350 mm

**SKU:** 281809

Mer information

## Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfERIC

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 98 °C

Mobil tank: Nej

Övrig information: 1 rectangular opening approx. 400 x 720 mm in the folding segment; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 10000

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.990 mm

Invändig diameter: 2.500 mm

Total höjd: 4.350 mm

Ytterdiameter: 2.640 mm

**Mer**

Isolerad: Ja

---