

10000 liter tank i Syrafast 316



204 000 SEK /st exkl moms

Additional information: Slurry; Type plate no longer available; Manufacturer's declaration available; Diameter manhole cylinder 600 mm; 1 tank with a smaller dent in the lower bottom (see photos); 2 more identical containers are available on request

Volumetric volume (L): 10.000 L

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single jacketed with heat-exchanger
Heat exchanger: yes
Insulation: no
Mobile tank: no

Total discharge: yes
Volume: 20 L
Max Overpressure: 3 Bar
Max. working temperature: 80 °C
Documents included: no

Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Outlet of tank: flange DN80
Agitator: yes

Power: 3
Cylinder: 4 mm
Bottom: 4 mm
Internal diameter tank: 2.500 mm
Cylinder height: 2.000 mm

Total height of tank: 3.800 mm
Empty weight tank: 1.100

SKU: 308719

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 80 °C

Mobil tank: Nej

Övrig information: Slurry; Type plate no longer available; Manufacturer's declaration available; Diameter manhole cylinder 600 mm; 1 tank with a smaller dent in the lower bottom (see photos); 2 more identical

Övrig information2: containers are available on request; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 10000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 2.000 mm
Invändig diameter: 2.500 mm
Total höjd: 3.800 mm

Omrörare

Kraft (kW): 3

Tjocklek på tank

Botten: 4 mm
Cylinder: 4 mm

Mer

Isolerad: Nej
Vikt: 1.100