

## 10000 liter tank i Syrafast 316



**207,000,00 kr /st exkl moms**

**Additional information:** Slurry; Type plate no longer available; Manufacturer's declaration available; Diameter manhole cylinder 600 mm; 1 tank with a smaller dent in the lower bottom (see photos); 2 more identical containers are available on request

**Volumetric volume (L):** 10.000 L

**Pressure in tank:** ATM - atmosferic  
**Max. temperature (°C):** 80 °C  
**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical  
**Configuration:** single jacketed with heat-exchanger  
**Heat exchanger:** yes  
**Insulation:** no  
**Mobile tank:** no

**Total discharge:** yes  
**Volume:** 20 L  
**Max Overpressure:** 3 Bar  
**Max. working temperature:** 80 °C  
**Documents included:** no

**Technical drawing included:** no  
**Registration plate on the tank:** no  
**Flange for agitator:** no  
**Outlet of tank:** flange DN80  
**Agitator:** yes

**Power:** 3  
**Cylinder:** 4 mm  
**Bottom:** 4 mm  
**Internal diameter tank:** 2.500 mm  
**Cylinder height:** 2.000 mm

**Total height of tank:** 3.800 mm  
**Empty weight tank:** 1.100

**SKU:** 308719

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfäric

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 80 °C

Mobil tank: Nej

Övrig information: Slurry; Type plate no longer available; Manufacturer's declaration available; Diameter manhole cylinder 600 mm; 1 tank with a smaller dent in the lower bottom (see photos); we can't give any

Övrig information2: guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 10000

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## Dimensioner av tank

Cylinderhöjd: 2.000 mm  
Invändig diameter: 2.500 mm  
Total höjd: 3.800 mm

## Omrörare

Kraft (kW): 3

## Tjocklek på tank

Botten: 4 mm  
Cylinder: 4 mm

## Mer

Isolerad: Nej  
Vikt: 1.100