

## 100000 liter tank i Rostfritt 304



**722 000 SEK /st exkl moms**

**Article type:** second-hand storage tank

**Additional information:** we can't give any guarantees about the agitator

**Volumetric volume (L):** 100.000 L

**Ra inner weld:** 0,80

**Finish stainless steel:** 2B

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated



**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Top type:** conical

**Shape of tank:** conical

**Bottom type:** conical

**Bottom outlet:** yes

**Total discharge:** yes

**Fixation points:** on skirt

**Insulation material:** rockwool

**Outer jacket (ornamental wall):** RVS 304

**Manway(s):** RVS 304

**Gasket manway(s):** unknown

**Fixation point(s):** RVS 304

**Wet parts agitator(s):** SS AISI 304 (V2A)

**Suitable for food industry:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** cylinder

**Hinged lid:** yes

**Outlet type:** DIN11850

**Outlet of tank:** DN65

**Agitator:** yes

**Agitator type:** propeller agitator

**Position engine:** in the bottom

**Number of revolutions:** 725/42 - 1470/86

**Power:** 2.7/5.5

**Voltage:** 400 V - three-phase

**Current:** 9.20/11.00

**Insulation body:** yes

**finish of the outer jacket:** welded  
**Insulation thickness:** 50  
**Internal diameter tank:** 4.000 mm

**Distance from outlet to ground:** 900 mm  
**Outer diameter tank:** 4.135 mm  
**Cylinder height:** 8.000 mm  
**Total height of tank:** 10.830 mm  
**Total outer width:** 4.300 mm

**Total outer length:** 11.000 mm  
**Empty weight tank:** 8.000

**SKU:** 296642

## Mer information

## Beskrivning av produkt

Livsmedelsklassad: Ja  
Material: Rostfritt 304  
Modell: Vertikal  
Nyttillverkad/Begagnad: Begagnad  
Arbetstryck i tank: ATM – atmosferic  
Finish rostfritt stål: 2b  
Konfiguration: insulated  
Mobil tank: Nej  
Övrig information: we can't give any guarantees about the agitator  
Omrörare: Ja  
Ra innersvets: 0,80  
Tankens form: conical  
Total urtappning: Ja  
Typ av botten: conical  
Uppvärmning/kylning: Nej  
Vätskeberörd yta: SS AISI 304 (V2A)  
Volym i liter: 100000

## Utrustning

Dokument finns: Nej  
Fläns för omrörare: Nej  
Märkskylt: Nej  
Livsmedelsklassad: Ja  
Teknisk ritning finns: Nej  
Utloppstyp: DIN11850

## Översikt material

Material: Rostfritt 304  
Fixeringspunkt(er): RVS 304  
Isoleringsmaterial: Rockwool  
Material vätskeberörd del på omrörare: SS AISI 304 (V2A)  
Ytterbeklädnad: RVS 304

## Dimensioner av tank

Cylinderhöjd: 8.000 mm  
Invändig diameter: 4.000 mm  
Mått utlopp till marken: 900 mm  
Total höjd: 10.830 mm  
Ytterdiameter: 4.135 mm

## Omrörare

Kraft (kW): 2.7/5.5  
Position motor: in the bottom  
Typ av omrörare: propeller agitator  
Varvtal: 725/42 - 1470/86  
Spänning (Volt): 400 V - three-phase

## Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded  
Isolering mantel: Ja  
Isoleringsmaterial: Rockwool

## Mer

Isoleringstjocklek OW: 50  
Isolerad: Ja  
Vikt: 8.000