

## 100000 liter tank i Rostfritt 304



**702 000 SEK /st exkl moms**

**Additional information:** PH glycerin; Electrical trace heating using external heating cables (no guarantee of functionality); Manhole diameter 600 mm (manhole cover may no longer exist); some residues of previous content

**Volumetric volume (L):** 100.000 L

**Pressure in tank:** ATM - atmosferic  
**Max. temperature (°C):** 60 °C  
**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical  
**Configuration:** insulated  
**Heat exchanger:** no  
**Insulation:** yes  
**Mobile tank:** no

**Total discharge:** yes  
**Documents included:** no  
**Technical drawing included:** no  
**Registration plate on the tank:** yes  
**Flange for agitator:** no

**Position of manway:** cylinder  
**Outlet of tank:** 80  
**Top:** 5 mm  
**Bottom:** 9 mm  
**Internal diameter tank:** 2.900 mm

**Cylinder height:** 15.140 mm

**SKU:** 278485

Mer information

## Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfERIC

Konfiguration: insulated

Max. arbetstemperatur: 60 °C

Mobil tank: Nej

Övrig information: PH glycerin; Electrical trace heating using external heating cables (no guarantee of functionality); Manhole diameter 600 mm (manhole cover may no longer exist); some residues of previous content

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 100000

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Rostfritt 304

## Dimensioner av tank

Cylinderhöjd: 15.140 mm

Invändig diameter: 2.900 mm

## Tjocklek på tank

Botten: 9 mm

Topp: 5 mm

**Mer**

Isolerad: Ja

---