

100000 liter tank i Syrafast 316



937,000,00 kr /st exkl moms

Additional information: chemistry; Partially small dents in heating coils, slight seizing with shallow depth at the bottom of the jacket.

Volumetric volume (L): 100.000 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 230 L

Max Overpressure: 6 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 150/50

Top: 18 mm

Cylinder: 18 mm

Bottom: 25 mm

Internal diameter tank: 3.600 mm

Outer diameter tank: 3.800 mm

Cylinder height: 9.870 mm

Total height of tank: 11.500 mm

Empty weight tank: 21.000

SKU: 441602

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: chemistry; Partially small dents in heating coils, slight seizure with shallow depth at the bottom of the jacket

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 100000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 9.870 mm
Invändig diameter: 3.600 mm
Total höjd: 11.500 mm
Ytterdiameter: 3.800 mm

Tjocklek på tank

Botten: 25 mm
Cylinder: 18 mm
Topp: 18 mm

Mer

Isolerad: Nej
Vikt: 21.000