10085 liter tank i Rostfritt 304



91 000 SEK /st exkl moms

Additional information: Fragrance production (alcoholic scents); 2 loose bearing shells, Aisi 304; 1 manhole approx. 345 x 440 mm in the front bottom; 1 tank marbled down to the rear bottom, the other tank only the front bottom; Tanks were screwed to the frame of 2 similar tanks at the previous operator (we currently offer these tanks under order no. 8910; while stocks last)
Volumetric volume (L): 10.085 L

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 50 °C
Material wet parts: SS AISI 304 (V2A)

Model: horizontal
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Outlet of tank: available
Cylinder: 4 mm
Bottom: 5 mm
Internal diameter tank: 1.700 mm
Total height of tank: 2.000 mm

Total outer length: 4.950 mm

SKU: 408764

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Horisontell
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single-skin
Max. arbetstemperatur: 50 °C
Mobil tank: Nej
Övrig information: Fragrance production (alcoholic scents); 2 loose bearing shells, Aisi 304; 1 manhole approx. 345 x 440 mm in the front bottom; 1 tank marbled down to the rear bottom, the other tank only the front
Övrig information2: bottom; Tanks were screwed to the frame of 2 similar tanks at the previous operator (we currently offer these tanks under order no. 8910; while stocks last)
Omrörare: Nej
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 10085

Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Invändig diameter: 1.700 mm
Total höjd: 2.000 mm

Tjocklek på tank
Botten: 5 mm
Cylinder: 4 mm

Mer
Isolerad: Nej