1011 liter tank i Syrafast 316



23 000 SEK /st exkl moms

Additional information: Putty; Stainless steel 304 frame; manhole diameter approx. 410 mm; 1 filling pipe inside the container; some residues of previous content; traces of usage
Volumetric volume (L): 1.011 L
Pressure in tank: pressure
Max. pressure (Bar): 0,50 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 0,50 Bar

Max. temperature (°C): 50 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: DN25 DIN 11851
Internal diameter tank: 1.090 mm

Cylinder height: 770 mm
Total height of tank: 1.920 mm
Total outer width: 1.210 mm
Total outer length: 1.210 mm

SKU: 427661

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single-skin
Max. arbetstemperatur: 50 °C
Mobil tank: Nej
Övrig information: Putty; Frame, Aisi 304; Manhole diameter approx. 410 mm; 1 filling tube inside the container; some residues of previous content;traces of usage
Omrörare: Nej
Övertryck: 0,50 Bar
Total urtappning: Ja
Undertryck (vakuum): 0,50 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1011

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 770 mm
Invändig diameter: 1.090 mm
Total höjd: 1.920 mm

Mer
Isolerad: Nej