102000 liter tank i Rostfritt 304



364 000 SEK /st exkl moms

Article type: second-hand storage tank
Volumetric volume (L): 102.000 L
Ra inner weld: 0,80
Finish stainless steel: 2b
Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)
Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes

Mobile tank: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Top type: conical
Shape of tank: cylindrical
Bottom type: flat sloping 3 °
Total discharge: yes

Insulation material: Rockwool
Outer jacket (ornamental wall): galvanised steel
Manway(s): RVS 304
Gasket manway(s): unknown
Suitable for food industry: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: yes
Number of manways: 1

Position of manway: cylinder
Height manhole 1 (mm): 405 mm x H 505 mm
Tank outlet: inside Ø 100 mm
Outlet type: PIPE END
Total outlet valve: no, optional

Agitator: no, optional
Cylinder: 50
Insulation body: yes
finish of the outer jacket: riveted
Internal diameter tank: 3.140 mm

Outer diameter tank: 3.400 mm
Cylinder height: 13.250 mm
Total height of tank: 14.350 mm
Empty weight tank: 5.000

SKU: 380255

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Finish rostfritt stål: 2b
Konfiguration: insulated
Mobil tank: Nej
Omrörare: Nej
Ra innersvets: 0,80
Tankens form: cylindrical
Total urtappning: Ja
Typ av botten: flat sloping 3 °
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 102000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Ja
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 100 mm
Teknisk ritning finns: Nej
Utloppstyp: PIPE END

Översikt material

Material: Rostfritt 304
Isoleringsmaterial: Rockwool
Ytterbeklädnad: galvanised steel

Dimensioner av tank

Cylinderhöjd: 13.250 mm
Invändig diameter: 3.140 mm
Total höjd: 14.350 mm
Ytterdiameter: 3.400 mm

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: riveted
Isolering mantel: Ja
Isoleringsmaterial: Rockwool

Mer

Cylinder OW: 50
Isolerad: Ja
Vikt: 5.000