

1025 liter tank i Syrafast 316



130,000,00 kr /st exkl moms

Additional information: Pharmacy; Diameter handhole appr. 145 mm

Volumetric volume (L): 1.025 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 41 L

Max Overpressure: 2,50 Bar

Max. working temperature: 130 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 47

Cylinder: 8 mm

Bottom: 7,20 mm

Internal diameter tank: 1.150 mm

Outer diameter tank: 1.270 mm

Total height of tank: 2.200 mm

SKU: 299792

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 130 °C

Mobil tank: Nej

Övrig information: Pharmacy; Diameter handhole appr. 145 mm; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 2 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1025

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 1.150 mm

Total höjd: 2.200 mm

Ytterdiameter: 1.270 mm

Tjocklek på tank

Botten: 7,20 mm

Cylinder: 8 mm

Mer

Isolerad: Ja