Revisions					
Rev	Description	Zone	Date	Drawn	Checked

Geometrical volume	10300 ℓ	Geometrical volume - jacket	-
Working pressure	Atmospheric	Working pressure - jacket	-
Working temperature	-10/80°C	Working temperature - jacket	-
Maximum density	1.2kg/dm³	Jacket pressure drop	-
Tare mass	484 kg	Material	1.4307 / AISI 304L
Equipment output/voltage	-	Year of manufacture	2018

Straightness, flatness and parallelism - EN 13920 F								Linear dimensions - EN 13920 B							
≥30 ≤120	>120 ≤400	>400 ≤1000	>1000 ≤2000	>2000 ≤4000	>4000 ≤8000	>8000 ≤12000	>12000 ≤16000	≥2 ≤30	>30 ≤400	>400 ≤1000	>1000 ≤2000	>2000 ≤4000	>4000 ≤8000	>8000 ≤12000	>12000 ≤16000
1	1.5	3	4.5	6	8	10	12	±1	±2	±3	±4	±6	±8	±10	±12

Surface	Outside	Matt 2B	Weld. seams	Outside	Strip grinded 2x20 Ra<1,6
	Inside	Matt 2B		Inside	Strip grinded 2x20 Ra<1,6

1.6	Drawn: **K.N.**	Scale 1:35	Weight 484.1	1.4307 / AISI 304L	
	Checked: **K.I.**	10300L			
	Approved: **D.M.**		Rev	10.9.2018 г.	Lang Eng / Sheet 2/2